

SPECIFICATIONS FOR RACK CABINET (1 UNIT)	
Rack Units:	48 U
Rack Mount Depth:	Standard Depth: 29.125" (740 mm) Adjustment Range: 6" to 30" in 1" increments (152 - 762 mm) Internal Space: 37.75" (959 mm) Front Space: 2.875" (73 mm)* Rear Space: 6.375" (162 mm)* *Measured with installation depth of 29.125" (740 mm)
Weighted Capacity:	750+ kgs (Rated capacity on leveling feet without casters)
Rack Outside Dimensions:	D x W 39" x 23.5" (1000 x 597 mm)
Included Hardware:	(40) 12-24 cage nuts (40) 12-24 x 3/8" screws (2) keys
Hole Type:	EIA 3/8" square holes
Rack Post Shape:	L Shape
Rack Ventilation:	76% perforation on doors
Rack Doors:	Removable, lockable and reversible
Rack Sides:	Removable and lockable
Rack Casters:	Standard casters with leveling feet NOTE: Casters are only for positioning an empty rack They aren't meant to support the rack when it's loaded with equipment
Finish:	Black, textured powder coat
Cage Nut Tool:	Mandatory and compatible to model.
Cooling Fans:	Number: 6 Axial AC fans Dimensions: 120 mm x 120 mm x 38 mm Fan tray dimensions: 17.16" W (435mm) X 17.31" (439mm) Fan Speed: 2000/2400 rpm
Power:	Rating: 240VAC Integrated power strip with surge protect